



# SK 11

## RIG INFORMATION

Arverne Drilling SK 11 is a highly mobile, trailer mounted, workover rig. The rig has been designed to reduce footprint and environmental impacts, in full API and EC regulations compliance, and easy to mobilize. The SK11 has a long track record in workovers on geothermal and oil & gas wells.

### MAST

TYPE	Skytop 56 - 120 XF
HEIGHT	17,10 m
MAX. HOOK LOAD	45 metric tonnes
MAX. DYN. LOAD	33 metric tonnes

### DRAWWORKS

TYPE	SkyTOP H1 32-32
CAPACITY	228 HP
MAX RPM	211 rpm
BREAKING LOAD	41,1 Kgf

### TRAVELLING BLOCK

TYPE	Mac Kissick
MODEL	82 A
CAPACITY	50 T

### BLOW OUT PREVENTION

TYPE	Hydril
DIAMETER	4 1/16 to 13 3/8"

### MUD SYSTEM

ACTIVE TANK	2 x 25m <sup>3</sup> with hooper
MIXING TANK	4 m <sup>3</sup>
MUD PUMP	1 x Gardner Denver 800 l/min 1000 PSI 400 l/min PSI

### TRAILER

TYPE	Unic 2564
PTC	26 T
REAR AXLE	2

### ADDITIONAL EQUIPMENT

POWER SWIVEL	Bowen 1.5
GENERATOR	65 Kva - soundproof

- 2600 m tubings 2 7/8"
- Diesel fuel tank, compressor unit
- Offices, crew cabins, workshops etc.
- Surface eqpt (HP leaning, etc.)

