



SK 7

RIG INFORMATION

MAST

TYPE	Skytop 96-XF-210M
STRUTS	External
API CAPACITY	95 T as per API 4 E

MAST STORAGE

TYPE	Tubing storage
CAPACITY	3600 m d 2 7/8" doubled up, 3000m de 3 1/12 doubled up

SUCKER RODS STORAGE No sucker rod storage

HOISTS

TYPE	Skytop H 1 4210-38 1
ENGINE	GM8 V 92
ENGINE POWER	368 Hp
LOADING HOIST	1" as per API RP 9B coeff 3 workloadl 55T 4 strands 80T 6 strands
PIGGING CAPACITY	9/16" 3000m

TRUCK

TYPE	Skytop RR 400 type 418
WEIGHT	40T category-1 convoy
FLOOR	Height adjustable to 2,60m
SURFACE AREA	3,00x2,70m

UTILITIES

SET-UP	<ul style="list-style-type: none"> Low-loader (for transport) foreman's office (12'), locker-room/facilities container (28'), container (12')
GENERATOR	90 Kva

ACCESSORIES

- 19-ton Iveco trailer equipped with a 3-ton hydraulic crane
- Tube handling equipment (2 3/8 EU to 3 1/2 tubing)
- Trailer handling equipment (5/8 to 1")
- Tube clamping equipment (Foster 58-93 hydraulic wrench)
- Trailer blocking equipment (Bowen pigging blocking wrench)
- Pigging equipment and train with SAS and pigging cross
- Low-loader trailer with utilities

BOP / KOOMEY UNIT

- Hydril GK or GKM and Trojan 7 - 1/16" 3000 (annulus and double rams)
- Type 80 closing unit with remote panel control
- Skid test stump for 7 1/16-5000 and 3000 with testing shafts

PUMP UNIT

SET-UP	Mounted on low-loader trailer with pump store
TYPE	Gardner Denver -triplex-PA 8BFB with 350l/mn to 1110 l/ mn intermittent service type plungers
ENGINE	Soundproof GM 6 V 92 diesel engine with 420 HP
BAY	Control bay 2x1m ³

OPTIONAL EQUIPMENT

- Cabled power swivel Bowen 2,5 S type, 45 Short Ton at 100 RPM. Soundproof 4-71 adapted GM power unit
- Bin capacity 3*30 m3 with mixing hooper
- Drilling rods 2 3/8 et 2 7/8 IF
- BOP annulus 11 - 3000